

ELT manufactures safe and high-quality Personnel Baskets. These products are **designed**, **fabricated**, **tested and certified to exceed ASME and OSHA standards**. If your question is not answered below please do not hesitate, contact us directly. We are more than happy to answer your question.

Is the test weight required?

- Federal OSHA regulations require a trial lift and inspection before EVERY use.
- A trial lift is performed at 125% of the platform's rated capacity.
- ELT provides an optional matching Test Weight for each of our Personnel Basket models.

 These Test Weights use a quick release system that provide a fast and easy way to mate both units.

What is the load rating requirement for each occupant?

- · Federal OSHA regulations require an overall rated load.
- There may be other requirements for your application. For example, the Washington State rating requirement is 500 lbs. for the first person and 250 lbs. for each additional person.

Are the platforms load tested?

All of ELT's Personnel Baskets are load tested prior to shipping and include a load test certificate.

Are the bridles certified and properly tagged?

- All ELT bridles are load tested, certified and specially tagged per ASME B30.23, certification is supplied.
- ELT's Standard Personnel Baskets come "Lift Ready."

Are 5th leg bridles required?

- OSHA and ASME do not require a 5th leg bridle, however some regulations may require one.
- · ELT offers this bridle type as an option upon request.

Is overhead protection required by OSHA?

- Federal OSHA regulations requires overhead protection ONLY if there is a danger of falling objects from above.
- Overhead protection can be provided for ELT Personnel Baskets as an option.

Is the platform design wind resistant?

• Yes, the unit is wind resistant due to the use of expanded metal sides.

Are U.S. and Canada Regulations the same?

- No, U.S. follows OSHA 29 CFR Subpart CC Part 1926.1431 and Canada follows WCB
- Standards WPL 2-2004.standards, Canada follows WCB standards.



716.667.6833 **1.888.358.5438**

